

SPECIFICATIONS

		47LV35A	55LV35A
PANEL	Screen Size	47" (46.96" measured diagonal)	55" (54.64" measured diagonal)
	Panel Technology	IPS	IPS
	Aspect Ratio	16 : 9	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)	1,920 x 1,080 (FHD)
	Brightness	450cd/m ²	500cd/m ²
	Contrast Ratio	1,200:1	1,400:1
	Dynamic CR	500,000 : 1	500,000 : 1
	Viewing Angle (H x V)	178 x 178	178 x 178
	Response Time	12ms (G to G)	12ms (G to G)
	Surface Treatment	Hard coating (3H), Anti-glare treatment of the front polarizer (Haze 1%)	Hard coating (3H), Anti-glare treatment of the front polarizer (Haze 10%)
CONNECTIVITY	Life time	50,000 Hrs	60,000 Hrs
	Orientation	Portrait & Landscape	Portrait & Landscape
	Input (Rear)	Digital	DVI-D (1), HDMI (1) with HDCP for all input
		Analog	RGB (1), Component (RGB Shared), AV (RGB Shared)
		Audio	-
		External Control	RS232C (1), RJ45 (1), IR Receiver (1)
	Output (Rear)	USB	USB 2.0 (1)
		Digital	DVI-D (1)
		Audio	-
		External Control	RS232C (1)
PHYSICAL SPECIFICATION	Color	Black	Black
	Bezel Width	3.2mm (left/top) / 1.7mm (right/bottom)	2.25mm (left/top) / 1.25mm (right/bottom)
	Monitor Dimension (W x H x D)	1,044.9mm x 590mm x 89.9mm	1,213.4mm x 684.2mm x 88.5mm
	Weight (Head)	16.5kg	23kg
	Carton Dimensions (W x H x D)	1,164mm x 765mm x 239mm (Box outer size)	1,337mm x 828mm x 239mm (Box outer size)
	Packed Weight	21.5kg	30kg
	Handle	Yes	Yes
	VESA™ Standard Mount Interface	600mm x 400mm	600mm x 400mm
SPECIAL FEATURES	Temperature Sensor	Yes	Yes
	Cooling FAN	No	No
	Tile Mode	Yes, Up to 15 x 15	Yes, Up to 15 x 15
	Natural mode @Tile mode	Yes	Yes
	Source Selection	Digital (HDMI / DVI) / Analog (RGB) / Component / USB	Digital (HDMI / DVI) / Analog (RGB) / Component / USB
	Brightness / Contrast / Backlight	Yes	Yes
	Position / Size	Yes	Yes
	Auto Config / Phase	Yes	Yes
	ISM Method	Normal, Color Wash	Normal, Color Wash
	Input Label	Yes	Yes
ENVIRONMENT CONDITIONS	Auto Power / Source Memory	Yes	Yes
	DPM Select	Yes (Installation Menu)	Yes (Installation Menu)
	Energy Saving	Yes, Off / Minimum / Medium / Maximum / Screen Off	Yes, Off / Minimum / Medium / Maximum / Screen Off
	Smart Energy Saving	Yes	Yes
POWER	Operation Temperature	0°C ~ 40°C	0°C ~ 40°C
	Operation Humidity	10% ~ 80%	10% ~ 80%
	Power Supply	100-240V~, 50/60Hz	100-240V~, 50/60Hz
	Power Type	Built-in Power	Built-in Power
	Power Consumption	Typ.	130W
		Smart Energy Saving	85W
		DPM	0.7W
		Power Off	0.5W
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC	UL / cUL / CB / TUV / KC
	EMC	FCC Class "A" / CE / KCC	FCC Class "A" / CE / KCC
	ErP / Energy Star	NA / Yes (Energy Star 6.0)	NA / Yes (Energy Star 6.0)
MEDIA PLAYER COMPATIBILITY	External Media Player Attachable	Yes	Yes
SOFTWARE COMPATIBILITY	SuperSign-W/Lite	Yes	Yes
	SuperSign-C	Yes	Yes
ACCESSORY	Accessory	Remote Controller, Power cable, DVI Cable, Manual, IR Receiver, RS-232C Cable, Guide Bracket, Screw	Remote Controller, Power cable, DVI Cable, Manual, IR Receiver, RS-232C Cable, Guide Bracket, Screw
	Optional Accessory	Wall Mount (Landscape : WM-L640V, Portrait : WM-P640V) Frame Kit (Horizontal : FK-47V10, Vertical: FK-47V20)	Wall Mount (Landscape : WM-L640V, Portrait : WM-P640V) 600 x 400 (AP-WX60)



Super Narrow Bezel VIDEO WALL DISPLAY LV35A

47LV35A | 47" CLASS (46.96" measured diagonal)

55LV35A | 55" CLASS (54.64" measured diagonal)



Super Narrow Bezel

47LV35A : 4.9mm

55LV35A : 3.5mm

Lighter & Thinner Cabinet

47LV35A : Weight 16.5kg, Depth 89.9mm

55LV35A : Weight 23kg, Depth 88.5mm

Higher Brightness Uniformity 80%

Dynamic Video-wall Configuration

Video Wall S/W to freely configure the layout and content

Free S/W for Remote Monitor & Control

Remotely monitor display status & control

24/7 Operation

Brightness

47LV35A : 450cd/m²

55LV35A : 500cd/m²

Portrait & Landscape Mode

Interfaces

RGB in, HDMI in, DVI in,
RS232C in/out, RJ45, USB

DISPLAY


Super Narrow Bezel

47" super narrow bezel 4.9mm and 55" super narrow bezel 3.5mm video wall displays create visually stunning digital wall that is easily installed, maintained and managed.




Higher Brightness Uniformity

Brightness uniformity 80% ensures high-quality image delivered across displays.



Wide Viewing Angle

IPS panels have the better control of liquid crystal and in consequence, it allows you to watch the screen virtually at any angle.




Temperature Resistent Panel Temperature



SOFTWARE

SuperSign V for Dynamic Layout

- Use given templates to configure video wall layout easily
- Rotate, cut and edit content according to a defined layout
- Flexible content editing in various layouts is viable
- Scheduled-based content playback based on time and day
- Distribute content to media players as well



Free SuperSign C for Advanced Color Adjustment

- Intuitive GUI in SuperSign C S/W allows to measure and adjust color and brightness instantly on display
- Automatic white balancing of a video-wall display using a sensor





Free SuperSign C for Remote Monitor and Control

Intuitive GUI-based Remote Monitoring & Control via the networks and RS232 connection feature in SuperSign C S/W.



DIMENSION (unit : mm)



INTERFACE

