

Small Display for Versatile Uses

Small Signage 10SM3TB



The 10SM3TB is the compact touch screen that can be used in a wide range of places, such as a price tag on supermarket shelves, near cashiers in convenience stores or as a notification board in business spaces. Also, the display offers simple and efficient power management via PoE (Power-over-Ethernet).



Key Features

Convenient Maintenance



PoE & Low Power Consumption


PoE* allows the installer to connect the power and network using just one wire. This greatly simplifies the installation and maintenance processes in locations where adding a power outlet is expensive or prohibited.



* Power-over-Ethernet

Simple Network Management Protocol

SNMP support ensures convenient network management.



Connectivity Supports



BEACON

With Beacon and Bluetooth Low Energy (BLE) supported by the 10SM3TB, stores can provide coupons and information in real-time which increase interactivity with customers at the moment of truth.



SoftAP

The 10SM3TB with SoftAP software can operate as a wireless access point for mobile devices.



Enhanced Usability



Built-in Touch

Interactive process between users and displays with built-in touch, creates informative and lively user experience.



Support for Android Environment

The application which can be operated on the screen with customers can be developed and used based on Android OS.



5.9GB Internal Memory + SD Card

With 5.9GB of internal memory and an additional SD card slot, you can play a sufficient amount of content within the internal memory or additional storage.



Small Display for Versatile Uses



Screen Size
10"

10SM3TB

- Brightness : 400cd/m²
- Bezel : 14mm (Even Bezel)
- Depth : 29.7mm
- Interface : USB, SD Card, RJ45
- Special Features : Wi-Fi Built-in, K-Slot




Specifications

	10SM3TB	
PANEL	Screen Size	10 (10.1")
	Panel Technology	ADS
	Aspect Ratio	16 : 9
	Native Resolution	1,280 x 800 (HD)
	Brightness	Module : 450cd/m ² , SET : 400cd/m ² (W/Touch)
	Contrast Ratio	900 : 1
	Dynamic CR	x
	Viewing Angle (H x V)	160 x 160
	Surface Treatment	Hard Coating, 2H, Low Reflection (Front Polarizer)
	Guaranteed Operating Hour	16 Hours
CONNECTIVITY	Orientation	Portrait & Landscape
	Input	USB, SD Card
	Output	-
PHYSICAL SPECIFICATION	External Control	RJ45
	Bezel Color	Black
	Bezel Width	14mm (T/R/L/B)
	Monitor Dimension (W x H x D)	245.6 x 164.2 x 29.7mm
	Weight (Head)	0.73kg
	Carton Dimensions (W x H x D)	327 x 224 x 95mm
	Packed Weight	1.22kg
SPECIAL FEATURES	VESA™ Standard Mount Interface	50 x 50mm
		Key Operation (Home, Power Key Operation), DPM Select, File Play with USB, Wi-Fi Built-in, Local Time Auto Setting, Wake on LAN, Password Change, BEACON, Internal Memory (System 0.15GB + Free 5.7GB), K-Slot
ENVIRONMENTAL CONDITIONS	Operating Temperature Range	0 °C to 40 °C
	Operating Humidity Range	10 % to 90 %
	Power Supply	100-240V~, 50/60Hz
POWER	Power Type	Built-in Power, Adaptor
	Power Switch	Power/Home
	Power Consumption Typ.	10W
AUDIO	Audio Power	1W (1W x 1Ch) for Internal Speaker
STANDARD (CERTIFICATION)	Safety	UL / cUL / TUV
	EMC	FCC Class "A" / CE
	ErP / Energy Star	NA / Yes (Energy Star 6.0)
ACCESSORY	Basic	Adaptor, Manual (Web), ESG
	Optional	No

Dimension (unit : mm)


10"

245.6 x 164.2 x 29.7 /
0.73kg



Connectivity

- LAN / PoE
- DC-IN
- USB IN
- MICRO SD



Download LG Commercial Display Mobile App



More info www.lgcommercial.com

YouTube youtube.com/c/LGCommercialDisplay

LG may make changes to specifications and product descriptions without notice.

Copyright © 2015 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered of LG Corp.

The names of products and brands mentioned here may be the trademarks of their respective owners.

